



Features

- 256 Channels DMX
- 64 Chases of up to 64 steps
- 8 or 16 bit fixture movement
- 8 Shows of up to 500 events
- 64 Internal play back keys over 4 pages
- 16 Channels of analogue inputs.
- Can be used to play back Individual channels, Keys, Scenes, Chases or Shows.
- MIDI in / thru/ out
- Audio sync via internal microphone or external 1/4" jack.

Technical Specifications

- **Power Supply:**
115/230V AC nominal
(95-264V AC)
Frequency 48-62Hz
80w max.
- **Power Connector:**
Supplied with unterminated
3-core mains flex
- **Control Signals:**
0 -10 V analogue via female 25-pin D
Audio line level via 1/4" stereo jack
MIDI in, out and thru via 5-pin DIN
- **Control Output:**
USITT DMX512 via XLR 5pin
connector, female

Overview


The Replica is a partner product to Lightprocessor's QCommander256 controller.

It is designed for use in situations where further programming of the lighting is not envisaged and the requirement is simply to play back previously-recorded programmes, usually in an architectural application such as a museum or retail premises.

Programmes are originated on a QCommander256 and then transferred into the Replica via the PCMCIA memory card supplied. All functions of the QCommander256 are available in the Replica.

Please note: The Replica is not compatible with the QCommander 512

Physical Characteristics



Weights:	Dimensions (mm)	Packaging Dimensions (mm)
Net: 3.5kg Gross: x kg	485 x 230 x 45	560 (L) 260(D) 100 (H)



ORDER CODE	DESCRIPTION
042-770	LightProcessor Replica 256 inc. 512kB RAM card



Lightprocessor

20 Greenhill Crescent, Watford Business Park,
Watford, Herts, WD18 8JA U.K.

T: +44 (0)1923 698090 F: +44 (0)1923 698081

E: info@lightprocessor.co.uk www.lightprocessor.co.uk